

Dell 27 Video Conferencing Monitor - S2722DZ Dell 24 Video Conferencing Monitor - S2422HZ



These easy-to-use 27" / 23.8" monitors are made for video calls with a built-in pop-up camera, noise-cancelling microphones and dual 5W speakers.. Available in both QHD (S2722DZ) and FHD resolution (S2422HZ).

High tech made simple

Outstanding value: Connecting virtually with friends and co-workers gets a major upgrade with the monitor's built-in camera, noise-cancelling microphones and dual 5W speakers. You'll enjoy amazing video clarity and crystal-clear sound.

The power of USB-C: Versatile USB-C connectivity delivers video, audio and data, and charges your laptop with up to 65 watts of power (even when the monitor is off) with the Always On Power Delivery feature. Plus, with just one cord, you'll have a clutter-free desk space.

Privacy when you want it: A super clear 5MP IR pop-up camera features facial recognition through Windows Hello for convenient, instant sign-on to Windows. The best part? The camera stays hidden until you're ready for video chatting or selfies.

Comfort comes first: A height-adjustable stand and a monitor that tilts, swivels and pivots so you look your best and feel your best for all-day conferencing.

Everyday elegance

A stunning setup: It brings a blend of great style and quality into every living space with a modern, sleek design. Plus, In-Plane Switching (IPS) technology together with 99% sRGB color coverage lets you see extraordinary colors across a wide viewing angle.

Perfect ports: Charging and connecting your storage devices, mobile phones and other peripherals just got easier with a conveniently placed, quick-access USB 3.2 Gen 1 Type-A port.

Keep everything in order: Stay organized between applications, emails and windows on one screen using Dell Easy Arrange.

Next-level eye comfort: ComfortView Plus is an always-on, built-in low blue light screen that optimizes eye comfort by reducing potentially harmful blue light emissions while delivering excellent color accuracy.

A brand you can rely on

As the No.1 monitor company worldwide^{*} we take pride in our unyielding commitment to quality and the utmost satisfaction of our customers.

Minimize downtime with Dell's Advanced Exchange Service.²

Dell Premium Panel Exchange allows a free panel replacement during the Limited Hardware Warranty³ period even if only one bright pixel is found.

FOR MORE INFORMATION, VISIT DELL.COM/MONITORS



*Source: IDC Worldwide Quarterly PC Monitor Tracker, Q1 2021

Features & Technical Specifications

D	is	p	lay	
	_			

S2422HZ

S2722DZ

Newsite integrate integrate604.04 cm (2039)604.04 cm (2019)604.04 cm (2019)Active aligning and onto traits with an extra traits and trai	Display	52422NZ	52122DZ		
Panel technologyin-Plane Switching (PS): Articipate with 3H hardnessMaximum resolution1900/1800 at 75Hz2560/1440 at 75HzAspect ratio16.9250 cdm²2560/1440 at 75HzAspect ratio0.2714 smm 8.02745 mm 8.02745 mm0.2331 mm 8.02331 nmBrightness (typical)250 cdm²350 cdm²Color agent (typical)150.7 million oolrs7Contrast ratio (typical)1,000 : 17Typical viewing angles (vertical / horizontal)179/178°White ED edgelight systemResponse time (typical)1.000 : 17WebcamIntegrated 5 Mega Pael pap-up IR comeraWhite ED edgelight systemWebcamIntegrated 5 Mega Pael pap-up IR comeraVestameMacrophonesNaise Cancelling Dual MicrophonesVestameAudio Output2 k WiVestame solution/ with Floker-free screenDid Display Manager compatibilityYes, supports AMD FreeSyne ^{7M} technology with Horiz-train port 1.1 k Just 5 2.0 m 1.0 screent with DisclapPort 1.2 USB 52.0 m 1.0 scree	Viewable image size (diagonal)	60.47 cm (23.8")	68.47 cm (27.0")		
Maximum resolution 1920x1080 at 75Hz 2560x1440 at 75Hz Aspect ratio 159 Pixel pitch 0.23745 mm x 0.2745 mm 0.2331 mm x 0.2331 mm Fightness (typical) 280 cdm ² 350 cdm ² Color gamut (typical) 280 cdm ² 350 cdm ² Color depth 10.775 million colors	Active display area (horizontal x vertical)	527.04 mm x 296.46 mm (20.75" x 11.67")	596.7 mm x 335.7 mm (23.49" x 13.21")		
Apped ratio 16-9 Pixel pitch 0.2745 mm x 0.2745 mm 0.2331 rm x 0.2331 rm Brightness (typical) 0.95% srG8 Color genut (typical) 16.7 million colors Color depth 16.7 million colors Seponse time (typical) 4ms gray to gray in extreme mode Beconse time (typical) 4ms gray to gray in extreme mode Seconse time (typical) 4ms gray to gray in extreme mode Microphones Noise Cancelling Dual Microphones Audio Output Ves. supports AMD FreeSync ¹⁶ /r technology with ref=rein rate of 75Hz TUV-certified Ves. ComfortView Plus' (Hardware Solution) with Flicker-free screen Dell Display Manager compatibility Ves. Supports AMD FreeSync ^{16/4} technology with ref=rein rate of 75Hz Stand edjustability Ves. Support AMD FreeSync ^{16/4} technology with ref=rein rate of 75Hz Stand solution Ves. ComfortView Plus' (Hardware Solution) with Flicker-free screen Stand edjustability Ves. Support AMD FreeSync ^{16/4} technology with ref=rein rate of 75Hz Stand solution Ves. 100 mm x 100 mm Stand fes	Panel technology	In-Plane Switching (IPS); Anti-glare with 3H hardness			
Pice pice0.2745 mm x 0.2745 mm0.2331 mm x 0.2331 mmBrightness (typical)250 cdm²350 cdm²Color garut (typical)95% RQBColor garut (typical)167 million colorsContrast ratio (typical)100 : 1Typical viewing angles (vertical / horizontal)178º / 178ºResponse time (typical)100 : 1Response time (typical)100 : 1Response time (typical)162 million colorsColor depth162 million colorsWebcamIntegrated 5 Mega Pool pop-up IR cameraMicrophonesNoise Cancelling Dual MicrophonesAudio Output2 x SWAMD FreeSync TM technology with rel-sh rate of 75HzConnectivityYes, supports AMD FreeSync TM technology with rel-sh rate of 75HzTÜV-cortlided2 x SWAudio OutputYes, with Del Easy ArrangeConnectivityYes, with Del Easy ArrangeStand adjustabilityYes, with Del Easy ArrangeStand adjustabilityHeight adjustment up to 1100m, TR -5' / 21', Swie-Jor' / 30', Pivot - 90' / 90'Stand adjustabilityYes (16 Gbep) downstraam pot 1: X HUBI (15 Gbep) downstraam with BCI z Angeing ad 2A (maximum), 1 x USB 22 Gen 1 (5 Gbep) downstraam with BCI z Angeing ad 2A (maximum), 1 x USB 22 Gen 1 (5 Gbep) downstraam with BCI z Angeing ad 2A (maximum), 1 x USB 22 Gen 1 (5 Gbep) downstraam with BCI z Angeing ad 2A (maximum), 1 x USB 22 Gen 1 (5 Gbep) downstraam with BCI z Angeing ad 2A (maximum), 1 x USB 22 Gen 1 (5 Gbep) downstraam with BCI z Angeing ad 2A (maximum), 1 x USB 22 Gen 1 (5 Gbep) downstraam with BCI z Angeing ad 2A (maximum), 1 x USB 22 Gen 1 (5 Gbep) downstraam with BCI z Angeing ad 2A (maximum),	Maximum resolution	1920x1080 at 75Hz	2560x1440 at 75Hz		
Bightness (typical) 250 cdm² 350 cdm² Color gamut (typical) 99% sRQ8 Color depth 1,00: 1 Typical viewing angles (vertical / horizontal) 179° / 178° Response time (typical) 179° / 178° Response time (typical) 179° / 178° Response time (typical) 180° gray in extreme mode Backing Angles (vertical / horizontal) 180° gray in extreme mode Backing Angles (vertical / horizontal) 180° gray in extreme mode Backing Angles (vertical / horizontal) 180° gray in extreme mode Backing Angles (vertical / horizontal) 180° gray in extreme mode Backing Angles (vertical / horizontal) 180° gray in extreme mode Backing Angles (vertical / horizontal) 180° gray in extreme mode Microphones Noise Concolling Dual Microphones Audio Output 2 x SW Audio Dupt Yes, Comfort/wer Meir (Hardware Solution) with Flicker-free screen Dill biphay Manager compatibility Yes, Starger (Sdray) downstream with Starger (Sdray) downstre	Aspect ratio	16:9			
Color depth 99% aRGB Color depth 6.7 million colors Contrast ratio (typical) 100° : 1 Typical Viewing angles (vertical / horizonta) 178° / 178° Beaponse time (typical) 4mag ray to gray to gray in extreme mode Beachight LED edgedipti system While LED edgedipti system Microphones Noise Carcelling Dual Microphones	Pixel pitch	0.2745 mm x 0.2745 mm	0.2331 mm x 0.2331 mm		
Color depth 16.7 million colors Color depth 1,000 : 1 Typically leveling angles (vertical / horizontal) 178-/178- Response time (typical) 178-/178- Response time (typical) 178-/178- Response time (typical) LED edgelight system While LED edgelight system Nicrophones Noise Cancelling Dual Microphones Audio Output 2 x 5W AMD FreeSync TM Yes, supports AMD FreeSync TM technology with refreesh rate of 75Hz TÜV-certified Yes, controftive Plusi (Hardware Solution) with Ficker-free screen Del Display Manager compatibility Yes, with Del Easy Arrange Connectivity Yes (Suber (1 subs) 2 Gent (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream with BC12 distanging at 2A (maximum), 1 x USB 32 Gent 1 (5 Gbps) downstream po	Brightness (typical)	250 cd/m ²	350 cd/m ²		
Contrast ratio (typical) 1000 : 1 Typical viewing angles (vertical / horizontal) 175° / 178° Response time (typical) 4ms gray to gray in externe mode Backlight LED edgelight system While LED edgelight system Wickbarn Integrated 5 Mega Pole pop-up IR camera Microphones Noise: Second Microphones Audio Output 2x SW AMD FreeSync TM Yes, supports AMD FreeSync TM technology with refrees trate of 75Hz. TOV-certified Yes, confort/vew Plus' (Hardware Solution) with Flicker-free screen Del Display Manager compatibility Yes, with Del Easy Arrange Yes, Supports AMD FreeSync TM technology with refrees trate of 75Hz. Audio Output Stand adjustability Yes, With Del Easy Arrange Yes, Supports Arrange VESA mount compatible Yes, 100 mm x 100 mm Yes (50kps) downatesm with BC12 / Arading at 2A (maximum), 12 Stand adjustability Yes (solt management slot Yes (solt management slot Power Arrange Yes (solt management slot Yes (solt management slot VESA mount compatible Yes (solt management slot Yes (solt management slot Power Arrange Classies Solt Solt Solt Solt mow (Yes Solt are Solt Het Solt Solt Solt Solt mow (Ye	Color gamut (typical)	99% sRGB			
Typical viewing angles (vertical / horizontal) 178º / 178º Response time (vepical) 4ms gray to gray in extreme mode Backlight LED edgelight system With LED edgelight system Response time (vepical) Integrated 5 Mega Pole pop-up IR camera Microphones Noise Cancelling Dual Microphones Audio Output 2 X 5W Audio Output Yes, supports AMD FreeSync TM lechnology with -if-scale of 75Hz TOV-ortified Yes, with Del Easy Arrage Connectivity Yes, with Del Easy Arrage Stand adjustability Yes, Support AMD FreeSync TM lechnology with 25 2 Cent (S Gbep) downstream port, Power Delivery PD up to 65 W), x USB 32 Gen 1 (S Gbep) downstream port, 12 L X SMB C1 2 charging at 2A (maximum), 12 wort 32 Cent 15 Gbep) downstream port, 12 L X SMB C1 2 charging at 2A (maximum) or 10 WS SC 2 end 15 Gbep) downstream port, 12 L X SMB C2 cent 13 Gbep) downstream port, 12 L X SMB C1 2 charging at 2A (maximum), 12 wort 32 Cent 15 Gbep) downstream port, 12 L X SMB C2 cent 13 Gbep) downstream port, 12 L X SMB C1 2 charging at 2A (maximum) with 55 C 2 darging at 2A (maximum), 12 wort 32 Cent 13 Gbep) downstream port, 12 L X SMB C1 2 charging at 2A (maximum), 12 wort 32 Cent 15 Gbep) downstream port, 12 L X SMB C1 2 charging at 2A (maximum), 12 wort 32 Cent 13 Gbep) downstream port, 12 L X SMB C1 2 charging at 2A (maximum), 12 wort 32 Cent 13 Gbep) downstream port, 12 L X SMB C1 2 charging at 2A (maximum), 12 wort 32 Cent 13 Gbep) downstream port, 12 L X SMB C1 2 charging at 2A (maximum), 12 wort 32 Cent 15 Gbep) downstream port, 12 L X SMB C1 2 charging at	Color depth	16.7 million colors			
Response time (typical) 4ms gray to gray in extreme mode Backlight LED edgelight system White LED edgelight system Webcam Integrated 5 Mega Pixel pop-up IR camera Microphones Noise Cancelling Dual Microphones Audio Output 2 x 5W AMD FreeSync TM Yes, supports AMD FreeSync TM technology with refresh rate of 75Hz Did Display Manager compatibility Yes, confort/View Plus' (Hardware Solution) with Flicker-free screen Did Display Manager compatibility Yes, with Sel Easy Arrange Connectivity 12 USB-C (Alternate mode with DisplayPort 12, USB 3.2 Gen 1 (Gbps) downstraam port, 11 x HDM 14 port, 13 value in-outp or 12 value in-outp or	Contrast ratio (typical)	1,000 : 1			
Backlight LED edgelight system White LED edgelight system Webcam Integrated 5 Mega Pikel pop-up IR camera Microphones Noise Cancelling Dual Microphones Audio Output 2 x 5W AMD FreeSync TM Yes, supports AMD FreeSync TM technology with refresh rate of 75Hz TÜV-certified Yes, Comfort/lew Plus' (Hardware Solution) with Flicker-free screen Del Display Manager compatibility Yes, With Del Easy Arrange Connectivity 1 x USB-2 (Allemate mode with DisplayPort 12, USB 3.2 Cen 1 upstream port, Power Delivery PD Stand adjustability Height adjustment up to 110mm, Tit -5" / 21", Swivel -30" / 30", Pivot -90" / 90" Stand adjustability Height adjustment up to 110mm, Tit -5" / 21", Swivel -30" / 30", Pivot -90" / 90" Stand features Built-in cable management slot VESA mount compatible Yes (cable lock sold separately) Power consumption (Operational) 0 VVC for 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) free for y Class (A to G scale) Power consumption (Operational) (S2422HZ) 53.37 mm (Top); 7.33 mm (Lef/Right); 22.11 mm (Botom) Del for plane only (Constreamed height) (S2422HZ) 33.35 mm x 57.8 mm x 56.74 mm (Hz + x 24.06" x 2.23") Montor head with stand (compressed/extended height) (S2422HZ) 33.57 mm x 57.8 mm x 57.8 mm x 17.47 mm (Botom) Derviser onsumption (Operational) 3.8 kg (8.55 lbs) 5.18 kg (11.42 lbs)	Typical viewing angles (vertical / horizontal)	178º / 178º			
NoteCam Integrated 5 Mega Pixel pop-up. IR camera Microphones Noise Cancelling Dual Microphones Audio Output 2 x SW AMD FreeSyne TM Yes, supports AMD FreeSyne TM technology with refresh rate of 75Hz TÜV-certified Yes, comfort/view Plus' (Hardware Solution) with Flicker-free screen Dell Display Manager compatibility Yes, with Dal Easy Arrange Connectivity 1 x USB-C (Alternate mode with DisplayPort 1.2, USB 3.2 Gen 1 (upstream port, Power Delivery PD up to 65 W), 1 x USB 3.2 Gen 1 (Gobpa) downstream port, 1 x HDMI 1.4 port, 1 x LDP 1.2, 1 x Audio line-out port Stand adjustability Height adjustment up to 110mm, Till -5° / 21', Swikel -30° / 30°, Pivot -90° / 90° Stand features Built-in cable management slot VESA mount compatible Yes, 100 mm x 100 mm Security lock slot Yes (cable lock sold separately) Power AC input Valage/frequency/current Constructive Visits (K4 NG s cale) Q.2 W (Off Mode) 0.2 W (Standby Mode) D W (VGT) (S2422H2) 333 rm m (EdfRight); 21 rm (Gottom) Power consumption (Operational) (S2422H2) 533 rm m (EdfRight); 21 rm (Gottom) D W (VGT) (S2422H2) 533 rm m (EdfRight); 21 rm (Gottom) Panel onty (S2422H2) 533 rm m (FGRight); 21	Response time (typical)	4ms gray to gray in extreme mode			
Microphones Noise Cancelling Dual Microphones Audio Output 2 x 5W AMD FreeSync TM Yes, supports AMD FreeSync TM technology with refresh rate of 75Hz TÜV-certified Yes, comfortView Plus' (Hardware Solution) with Flicker-free screen Dell Display Manager competibility Yes, with Dell Easy Arrange Connectivity 1 x USB-C (Alternate mode with DisplayPort 1.2, USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum). 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum). 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum). 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum). 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum). 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum). 1 x USB 3.2 Gen 1 (5 Gbps) downstream with DC1.1 x PUI.2.1 x Audio line-out port Stand adjustability Height adjustment up to 110mm, Tit -5' / 21°, Swivel -30° / 30°, Phot -90° / 90° Stand features Bull-in cable management slot VESA mount compatible Yes, 100 mm x 100 mm Security lock slot Yes (cable lock sold separately) Power 00 VAC (p 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) (prop) Power construction (Gbd Monitor to active area) (S2422Hz) 5 S7 mm (Top); 7.43 mm (LeftRight); 21 mm (Bottom) Panel onty (S2422Hz) 5 S7 mm x 567.4 mm (H4.24 ME x 22.37) Monitor nead/extended height) S2422Hz) 5 S7 mm x 567.4 mm (H4.27 ME X 22.37) Monitor nead/e	Backlight	LED edgelight system	White LED edgelight system		
Audio Output 2 x 5W AMD FreeSync TM Yes, supports AMD FreeSync TM technology with refresh rate of 75Hz TÜV-certified Yes, ConfrottView Plus' (Hardware Solution) with Flicker-free screen Dell Display Manager compatibility Yes, with Dell Easy Arrange Connectivity 1 x USB-2 (Alternate mode with DisplayPort 1.2, USB 3.2 Gen 1 upstream port, Power Delivery PD up to 55 W), 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum), 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum), 1 x USB 3.2 Gen 1 (5 Gbps) downstream port, 1 x HDMI 1.4 port, 1 x DP 1.2, 1 x Audio line-out port Stand adjustability Height adjustment up to 110mm, Tit -5* / 21*, Swivel -30* / 30*, Pivot -90* / 90* Stand features Bull-in cable management stot VESA mount compatible Yes, 100 mm x 100 mm Security lock slot Yes (cable lock sold separately) Power 100 VAC to 2.40 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) [F Power consumption (Operational) 100 VAC to 2.40 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) [F Dell Vidtage/frequency/current F Cargott Vidth (Edge of Monitor to active area) (S2422HZ) 5.37 mm (Top); 5.38 mm (Left/Right); 21.7 mm (Bottom) Dimensions (HxWxD) S2422HZ) 233.57 mm x 557.8 mm x 557.8 mm x 174.7 mm (144* x 24.08* x 23*) Panel only (S2422HZ) 233.57 mm x 557.8 mm x 557.8 mm x 174.7 mm (145*' 719.33* x 21.17* x 6.88*) Waith 3.88 kg (6.55 lbs) 5.	Webcam	Integrated 5 Mega Pixel pop-up IR camera			
AMD FreeSync TM Yes, supports AMD FreeSync TM technology with refresh rate of 75Hz TÜV-certified Yes, Comfort/view Plus' (Hardware Solution) with Flicker-free screen Dell Display Manager compatibility Yes, with Dell Easy Arrange Connectivity 1 x USB-2 (Alternate mode with DisplayPort 1.2, USB 3.2 Gen 1 upstream port, Power Delwery PD up to 55 W), 1 x USB 3.2 Gen 1 (6 Geps) downstream with BC1.2 charging at 2A (maximum), 1 x USB 3.2 Gen 1 (6 Geps) downstream port, 1 x HDMI 1.4 port, 1 x DP 1.2, 1 x Audio line-out port Stand adjustability Height adjustment up to 110mm, Tit -5* / 21*, Swivel -30* / 30*, Pivot -90* / 90* Stand features Bull-in cable management slot VESA mount compatible Yes, 100 mm x 100 mm Security lock slot Yes (Cable lock sold separately) Power 100 VAC to 2.40 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) free for 18 W (Max) AC input voltage/frequency/current [S 222 W (Off Mode) 0.2 W (Standby Mode)] 0.2 W (Off Mode) 0.3 W (Standby Mode)] Foreyr Efficiency [S 222 ZZ 2] Z 3.7 mm (Top); 5.38 mm x 56.74 mm (14.4* x 24.06* x 2.3*) 2.8 (Mode) 149 W (Max) Dimensions (HxWxD) [S 222 ZZ 2] Z 3.77 mm (Top); 5.38 mm x 56.74 mm (14.4* x 24.06* x 2.3*) 2.8 (Z 222 ZZ 2) Z 2.3*) Panel only [S 222 ZZ 2] Z 3.73 mm x 56.74 mm x 61.74 mm (14.4* x 24.06* x 2.3*) 2.8 (Z 222 ZZ 2) Z 2.2*) Monitor head w	Microphones	Noise Cancelling Dual Microphones			
TÜV-certified Yes, ConfortView Plus' (Hardware Solution) with Flicker-free screen Dell Display Manager compatibility Yes, with Dell Easy Arrange Connectivity 1 x USB-2 (Alternate mode with DisplayPort 1.2, USB 3.2 Gen 1 upstream port, Power Delivery PD up 065 W), 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum), 1 x USB 3.2 Gen 1 (5 Gbps) downstream port, 1 x HDMI 1.4 port, 1 x DP 1.2, 1 x Audio line-out port Stand adjustability Height adjustment up to 110mm, Tit -5' / 21', Swivel -30' / 30', Pivot -90' / 90' Stand features Bull-in cable management slot VESA mount compatible Yes, (cond WAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum)) Security lock slot Too VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum)) Power Difference AC input voltage/frequency/ourrent 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum)) Energy Efficiency Class (A to G scale) Difference Dever consumption (Operational) (S2422HZ) 5.37 mm (Top): 7.43 am (Left/Right); 21.71 mm (Bottom) Dimensions (HxWxD) (S2422HZ) S2.57 mm x 557.8 mm x 567.4 mm (12.74" x 21.17" x 2.23") Panel only (for VESA) 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and cables with full packaging 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and cables with full packaging 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and cables with full packaging 3.88 kg (8.55 lbs)<	Audio Output	2 x 5W			
Dell Display Manager compatibility Yes, with Dell Easy Arrange Connectivity 1 x USB-C (Alternate mode with DisplayPort 1.2, USB 3.2 Gen 1 upstream port, Power Delivery PD up to 65 W), 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum). 1 x USB 3.2 Gen 1 (5 Gbps) downstream port, 1 x HDM 1.4 port, 1 x DP 1.2, 1 x Audio line-out port Stand adjustability Height adjustment up to 110mm, Tilt -5° / 21°, Swivel -30° / 30°, Pivot -90° / 90° Stand features Bull-In cable management slot VESA mount compatible Yes, (10 mm x 100 mm Security lock slot Yes (cable lock sold separately) Power 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) Power consumption (Operational) 00 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) Dell Object Prover consumption (Operational) (S422HZ) 5.37 mm (Top); 5.38 mm (Left/Right); 21.7 mm (Bottom) Dimensions (HXWXD) (S2422HZ) 323.57 mm x 537.8 mm x 56.74 mm (12.74° x 21.17° x 2.37) Monitor head with stand (compressed/extended height) 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Panel only (for VESA) 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and cables with full packaging 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and cables with full packaging 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and	AMD FreeSync [™]	Yes, supports AMD FreeSync TM technology with refresh rate of 75Hz			
Connectivity 1 x USB-C (Alternate mode with DisplayPort 1.2, USB 3.2 Gen 1 upstream port, Power Delivery PD up to 65 W), 1 x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum), 1 x USB 3.2 Gen 1 (5 Gbps) downstream port, 1 x HDMI 1.4 port, 1 x DP 1.2, 1 x Audio line-out port Stand adjustability Height adjustment up to 110mm, Tilt -5° / 21°, Swivel -30° / 30°, Pivot -90° / 90° Stand features Built-in cable management slot VESA mount compatible Yes, 100 mm x 100 mm Socurity lock slot Yes (cable lock sold separately) Power AC input voltage/frequency/current Energy Efficiency Class (A to G scale) D Power consumption (Operational) 02 W (Off Mode) 0.2 W (Standby Mode) 0.2 W (Off Mode) 0.3 W (Standby Mode) D 0 02 VCR1 Mode) 0.2 W (Off Mode) 0.3 W (Standby Mode) D 0 02 VCR1 Mode) 137 W (Max) 19.26W (On Mode) 149 W (Max) Border Width (Edge of Monitor to active area) (S2422HZ) 5.37 mm (Top); 5.38 mm x 56.74 mm (12.74° x 2.117° x 2.83°) (S2722D2) 7.37 mm (Top); 7.43 mm (Left/Right); 21.7 mm (Bottom) Dimensions (HXWXD) (S2422HZ) 323.657 mm x 537.8 mm x 57.8 mm x 174.7 mm (14.9° / 19.23° x 21.17° x 8.87) (S2722D2) 206.54 mm x 51.6 mm x 51.6 mm x 174.7 mm (14.9° / 19.23° x 21.17° x 8.87) Weight Sa8 kg (8.55 lbs) 5.18 kg (11.42 lbs)	TÜV-certified	Yes, ComfortView Plus1 (Hardware Solution) with Flicker-free screen			
up to 65 W), 1x USB 3.2 Gen 1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum), 1 x USB 3.2 Gen 1 (5 Gbps) downstream port, 1 x HDMI 1.4 port, 1 x DP 1.2, 1 x Audio line-out port Stand adjustability Height adjustment up to 110mm, Tilt -5" / 21°, Swivel -30° / 30°, Pivot -90° / 90° Stand features Built-in cable management slot VESA mount compatible Yes, 100 mm x 100 mm Security lock slot Yes (cable lock sold separately) Power AC Input voltage/frequency/current AC Input voltage/frequency/current 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) Power consumption (Operational) D D D D D D/Q/W 0.2 W (Off Mode) 0.3 W (Max) Border Width (Edge of Monitor to active area) (S2422HZ) 5.37 mm (Top); 5.38 mm (Left/Right); 21.7 mm (Bottom) Scr22D2) 7.37 mm (Top); 5.38 mm x 567.4 mm (14.4* x 24.08* x 2.23") Monitor head with stand (compressed/extended height) (S2422HZ) 235.3 mm x 537.8 mm x 567.4 mm (14.4* x 24.08* x 2.23") Weight 388 kg (8.55 lbs) 5.18 kg (11.42 lbs) 9.46 kg (20.85 lbs) Panel only (S2422HZ) 7.37 mm (Fog), 5.38 mm x 174.7 mm (14.9" / 19.23" x 21.17" x 6.88") (S2722DZ) 27.85 M m x 611.6 mm x 57.4 mm (14.4* x 24.08* x 2.23") (S2422HZ) 237.8 mm x 611.6 mm x 174.7 mm (Dell Display Manager compatibility	Yes, with Dell Easy Arrange			
Stand features Built-in cable management slot VESA mount compatible Yes, 100 mm x 100 mm Security lock slot Yes (cable lock sold separately) Power 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) D (D Action Voltage/frequency/current Energy Efficiency Class (A to G scale) 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) D (D Action Voltage/frequency/current Energy Efficiency Class (A to G scale) D (D Action Voltage/frequency/current Energy Efficiency Class (A to G scale) D (D Action Voltage/frequency/current Energy Efficiency Class (A to G scale) D (D Action Voltage/frequency/current Energy Efficiency Class (A to G scale) D (D Action Voltage/frequency/current Energy Efficiency Class (A to G scale) D (D Action Voltage/frequency/current Energy Efficiency Class (A to G scale) D (D Action Voltage/frequency/current Energy Efficiency Class (A to G scale) D (D Action Voltage/frequency/current Energy 25,37 mm (Top); 5.38 mm (Left/Right); 21.7 mm (Bottom) (S2722DZ) 7.37 mm (Top); 7.43 mm (Left/Right); 22.81 mm (Bottom) Dimensions (HxWxD) Panel only (S2422HZ) 323.57 mm x 537.8 mm x 56.74 mm (14.4* x 24.08* x 2.23*) (S2722DZ) 400.0 mm / 510.0 mm x 511.6 mm x 174.7 mm (15.75* / 20.08* x 24.08* x 6.88*) Weight Panel only (for VESA) Monitor head with stand (compressed/extended height) S.88 kg (8.55 lbs) 7.88 kg (17.37 lbs) 5.18 kg (11.42 lbs) 9.46 kg (20.85 lbs) 5.18 kg (11.42 lbs) 9.46 kg (20.85 lbs) S.18 kg (11.42 lbs) 9.46 kg (20.85 lbs) S.18 kg (17.37 lbs) 9.46 kg (20.85 lbs) S.18 kg (17.37 lbs) <	Connectivity	up to 65 W), 1 x USB 3.2 Gen1 (5 Gbps) downstream with BC1.2 charging at 2A (maximum). 1 x			
VESA mount compatible Yes, 100 mm Security lock slot Yes (cable lock sold separately) Power 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) representation (Operational) Power consumption (Operational) 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) representation (Operational) Border Width (Edge of Monitor to active area) 0.2 W (Off Mode) 0.2 W (Standby Mode) 18.26W (On Mode) 149 W (Max) Dimensions (HxWxD) S2422H2) 5.37 mm (Top); 5.38 mm (Left/Right); 21.7 mm (Bottom) (S2722D2) 7.37 mm (Top); 7.43 mm (Left/Right); 22.81 mm (Bottom) Panel only (S2422H2) 323.57 mm x 537.8 mm x 56.74 mm (14.74 * x 24.06* x 2.23°) (S2722D2) 365.84 mm x 56.74 mm (14.4* x 24.06* x 2.23°) (S2722D2) 365.84 mm x 56.74 mm (14.4* x 24.06* x 2.23°) (S2722D2) 365.84 mm x 56.74 mm (14.4* x 24.06* x 2.23°) (S2722D2) 400.0 mm x 511.6 mm x 56.74 mm (14.4* x 24.06* x 2.23°) (S2722D2) 400.0 mm x 510.0 mm x 611.6 mm x 174.7 mm (15.75* / 20.08* x 24.08* x 6.88*) Weight 3.88 kg (8.55 lbs) 7.88 kg (17.37 lbs) 5.18 kg (11.42 lbs) 9.46 kg (20.85 lbs) Monitor and cables with full packaging 3.88 kg (17.37 lbs) 9.46 kg (20.85 lbs) Fuvironmental compliance Energy STAR certified, RoHS-compliant, BFR/PVC-reduced monitor (excluding external cables), Arsenic-free glass and Mercury-free for the panel only. Standard service plan 3-year Advanced Exchange Service ² & Premium Panel Exchange What's Included Monitor panel, Stand fiser, Stand	Stand adjustability	Height adjustment up to 110mm, Tilt -5° / 21°,Swive	Height adjustment up to 110mm, Tilt -5° / 21°, Swivel -30° / 30°, Pivot -90° / 90°		
Security lock slot Yes (cable lock sold separately) Power 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) D D D Power consumption (Operational) 0.2 W (Off Mode) 0.2 W (Standby Mode) 0.2 W (Off Mode) 0.3 W (Standby Mode) Power consumption (Operational) 0.2 W (Off Mode) 0.2 W (Standby Mode) 0.2 W (Off Mode) 0.3 W (Standby Mode) Border Width (Edge of Monitor to active area) (S2422HZ) 5.37 mm (Top); 5.38 mm (Left/Right); 21.7 mm (Bottom) (S2722DZ) 7.37 mm (Top); 7.43 mm (Left/Right); 22.81 mm (Bottom) Dimensions (HxWxD) (S2422HZ) 323.57 mm x 537.8 mm x 56.74 mm (12.74" x 21.17" x 2.23") (S2722DZ) 365.84 mm x 611.6 mm x 56.74 mm (14.4" x 24.08" x 2.23") Monitor head with stand (compressed/extended height) (S2422HZ) 378.4 mm / 488.4 mm x 537.8 mm x 174.7 mm (14.9" / 19.23" x 21.17" x 6.88") (S2722DZ) 400.0 mm x 611.6 mm x 74.7 mm (14.9" / 19.23" x 24.08" x 6.88") Weight Panel only (for VESA) Monitor and cables with full packaging 3.88 kg (8.55 lbs) 7.88 kg (17.37 lbs) 5.18 kg (11.42 lbs) 9.46 kg (20.85 lbs) Environmental compliance Energy STAR certified, RoHS-compliant, BFR/PVC-reduced monitor (excluding external cables), Arsenic-free glass and Mercury-free for the panel only. Standard service plan 3-year Advanced Exchange Service ² & Premium Panel Exchange What's Included Monitor panel, Stand riser, Stand base, Power cable, USB Type-C to USB Type-C 3.2 Gen 1 cable, Quick setup guide, Safety / Environmenta	Stand features	Built-in cable management slot			
Power AC input voltage/frequency/current Energy Efficiency Class (A to G scale) Power consumption (Operational) 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) F 0.2 W (Off Mode) 0.2 W (Off Mode) 0.3 W (Standby Mode) 18.26W (On Mode) 137 W (Max) Border Width (Edge of Monitor to active area) (S2422HZ) 5.37 mm (Top); 5.38 mm (Left/Right); 21.7 mm (Bottom) (S2722DZ) 7.37 mm (Top); 7.43 mm (Left/Right); 22.81 mm (Bottom) Dimensions (HxWxD) Panel only (S2422HZ) 323.57 mm x 537.8 mm x 56.74 mm (12.74" x 21.17" x 2.23") (S2722DZ) 365.84 mm x 611.6 mm x 56.74 mm (14.4" x 24.08" x 2.23") Monitor head with stand (compressed/extended height) (S2422HZ) 378.4 mm / 488.4 mm x 537.8 mm x 174.7 mm (14.9" / 19.23" x 21.17" x 6.88") (S2722DZ) 400.0 mm / 510.0 mm x 611.6 mm x 174.7 mm (15.75" / 20.08" x 24.08" x 6.88") Weight Panel only (for VESA) Monitor and cables with full packaging 3.88 kg (8.55 lbs) 7.88 kg (17.37 lbs) 5.18 kg (11.42 lbs) 9.46 kg (20.85 lbs) Environmental compliance Energy STAR certified, RoHS-compliant, BFR/PVC-reduced monitor (excluding external cables), Arsenic-free glass and Mercury-free for the panel only. Standard service plan 3-year Advanced Exchange Service ² & Premium Panel Exchange What's Included Monitor panel, Stand pase, Power cable, USB Type-C to USB Type-C 3.2 Gen 1 cable, Quick setup guide, Safety / Environmental / Regulatory Information 'Comfort/Wew Plus feature reduces blue light emission and optimizes eye comfort, while delivering excellent coder asourage.	VESA mount compatible	Yes, 100 mm x 100 mm			
AC input voltage/frequency/current 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 2 A (maximum) F Energy Efficiency Class (A to G scale) D D F Power consumption (Operational) 0.2 W (Off Mode) 0.2 W (Standby Mode) 0.2 W (Off Mode) 0.3 W (Standby Mode) Border Width (Edge of Monitor to active area) (S2422HZ) 5.37 mm (Top); 5.38 mm (Left/Right); 21.7 mm (Bottom) Dimensions (HxWxD) (S2422HZ) 323.57 mm x 537.8 mm x 56.74 mm (12.74" x 21.17" x 2.23") Panel only (S2422HZ) 323.57 mm x 537.8 mm x 56.74 mm (14.4" x 24.08" x 22.37") Monitor head with stand (compressed/extended height) (S2422HZ) 378.4 mm / 488.4 mm x 537.8 mm x 174.7 mm (14.9" / 19.23" x 21.17" x 6.88") Weight S.18 kg (17.37 lbs) 9.46 kg (20.85 lbs) Panel only (for VESA) 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and cables with full packaging 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and cables with full packaging 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Standard service plan 3-year Advanced Exchange Service ² & Premium Panel Exchange What's Included Wonitor panel, Stand riser, Stand base, Power cable, USB Type-C to USB Type-C 3.2 Gen 1 cable, Quick setug guide, Safety / Environmental / Regulatory Information 'comtortview Plus feature reduces blue light emission and optimizes e	Security lock slot	Yes (cable lock sold separately)	Yes (cable lock sold separately)		
Dimensions (HxWxD) (S2722DZ) 7.37 mm (Top); 7.43 mm (Left/Right); 22.81 mm (Bottom) Panel only (S2422HZ) 323.57 mm x 537.8 mm x 56.74 mm (12.74" x 21.17" x 2.23") (S2722DZ) 365.84 mm x 611.6 mm x 56.74 mm (14.4" x 24.08" x 2.23") Monitor head with stand (compressed/extended height) (S2422HZ) 378.4 mm / 488.4 mm x 537.8 mm x 174.7 mm (14.9" / 19.23" x 21.17" x 6.88") (S2722DZ) 400.0 mm / 510.0 mm x 611.6 mm x 174.7 mm (15.75" / 20.08" x 24.08" x 6.88") Weight 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) 9.46 kg (20.85 lbs) Panel only (for VESA) 3.88 kg (17.37 lbs) 9.46 kg (20.85 lbs) Monitor and cables with full packaging T.88 kg (17.37 lbs) 9.46 kg (20.85 lbs) Environmental compliance Energy STAR certified, RoHS-compliant, BFR/PVC-reduced monitor (excluding external cables), Arsenic-free glass and Mercury-free for the panel only. Standard service plan 3-year Advanced Exchange Service ² & Premium Panel Exchange What's Included Monitor panel, Stand riser, Stand base, Power cable, USB Type-C to USB Type-C 3.2 Gen 1 cable, Quick setup guide, Safety / Environmental / Regulatory Information 'ComfortView Plus feature reduces blue light emission and optimizes eye comfort, while delivering excellent color accuracy.	AC input voltage/frequency/current Energy Efficiency Class (A to G scale)	0.2 W (Off Mode) 0.2 W (Standby Mode)	0.2 W (Off Mode) 0.3 W (Standby Model)		
Dimensions (HxWxD) Panel only (S2422HZ) 323.57 mm x 537.8 mm x 56.74 mm (12.74" x 21.17" x 2.23") (S2722DZ) 365.84 mm x 611.6 mm x 56.74 mm (14.4" x 24.08" x 2.23") Monitor head with stand (compressed/extended height) (S2422HZ) 378.4 mm / 488.4 mm x 537.8 mm x 174.7 mm (14.9" / 19.23" x 21.17" x 6.88") (S2722DZ) 400.0 mm / 510.0 mm x 611.6 mm x 174.7 mm (15.75" / 20.08" x 24.08" x 6.88") Weight	Border Width (Edge of Monitor to active area)				
Monitor head with stand (compressed/extended height) (S2722DZ) 365.84 mm x 611.6 mm x 56.74 mm (14.4" x 24.08" x 2.23") Monitor head with stand (compressed/extended height) (S2422HZ) 378.4 mm / 488.4 mm x 537.8 mm x 174.7 mm (14.9" / 19.23" x 21.17" x 6.88") Weight S2722DZ) 400.0 mm / 510.0 mm x 611.6 mm x 174.7 mm (15.75" / 20.08" x 24.08" x 6.88") Weight 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and cables with full packaging 7.88 kg (17.37 lbs) 9.46 kg (20.85 lbs) Environmental compliance Energy STAR certified, RoHS-compliant, BFR/PVC-reduced monitor (excluding external cables), Arsenic-free glass and Mercury-free for the panel only. Standard service plan 3-year Advanced Exchange Service ² & Premium Panel Exchange What's Included Monitor panel, Stand riser, Stand base, Power cable, USB Type-C to USB Type-C 3.2 Gen 1 cable, Quick setup guide, Safety / Environmental / Regulatory Information 'ComfortView Plus feature reduces blue light emission and optimizes eye comfort, while delivering excellent color accuracy.					
Weight 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Panel only (for VESA) 3.88 kg (8.55 lbs) 5.18 kg (11.42 lbs) Monitor and cables with full packaging 7.88 kg (17.37 lbs) 9.46 kg (20.85 lbs) Environmental compliance Energy STAR certified, RoHS-compliant, BFR/PVC-reduced monitor (excluding external cables), Arsenic-free glass and Mercury-free for the panel only. Standard service plan 3-year Advanced Exchange Service ² & Premium Panel Exchange What's Included Monitor panel, Stand riser, Stand base, Power cable, USB Type-C to USB Type-C 3.2 Gen 1 cable, Quick setup guide, Safety / Environmental / Regulatory Information		(S2722DZ) 365.84 mm x 611.6 mm x 56.74 mm (14.4" x 24.08" x 2.23") ´ (S2422HZ) 378.4 mm / 488.4 mm x 537.8 mm x 174.7 mm (14.9" / 19.23" x 21.17" x 6.88")			
Monitor and cables with full packaging 7.88 kg (17.37 lbs) 9.46 kg (20.85 lbs) Environmental compliance Energy STAR certified, RoHS-compliant, BFR/PVC-reduced monitor (excluding external cables), Arsenic-free glass and Mercury-free for the panel only. Standard service plan 3-year Advanced Exchange Service ² & Premium Panel Exchange What's Included Monitor panel, Stand riser, Stand base, Power cable, USB Type-C to USB Type-C 3.2 Gen 1 cable, Quick setup guide, Safety / Environmental / Regulatory Information 'ComfortView Plus feature reduces blue light emission and optimizes eye comfort, while delivering excellent color accuracy.	Weight				
Arsenic-free glass and Mercury-free for the panel only. Standard service plan 3-year Advanced Exchange Service ² & Premium Panel Exchange What's Included Monitor panel, Stand riser, Stand base, Power cable, USB Type-C to USB Type-C 3.2 Gen 1 cable, Quick setup guide, Safety / Environmental / Regulatory Information 'ComfortView Plus feature reduces blue light emission and optimizes eye comfort, while delivering excellent color accuracy.		S ()			
What's Included Monitor panel, Stand riser, Stand base, Power cable, USB Type-C to USB Type-C 3.2 Gen 1 cable, Quick setup guide, Safety / Environmental / Regulatory Information 'ComfortView Plus feature reduces blue light emission and optimizes eye comfort, while delivering excellent color accuracy.	Environmental compliance	oy i i i i i i i i i i			
Quick setup guide, Safety / Environmental / Regulatory Information ¹ ComfortView Plus feature reduces blue light emission and optimizes eye comfort, while delivering excellent color accuracy.	Standard service plan	3-year Advanced Exchange Service ² & Premium Panel Exchange			

Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.

³For a copy of the Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see Dell.com/warranty.

Technical specifications subject to change without prior notice.

Product availability varies by country. Please contact your Dell representative for more information.

Copyright 2021 Dell Inc. All rights reserved. Other trademarks or trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Reproduction in any manner whatsoever without express written permission from Dell Inc. is strictly forbidden.